

LIVE TO PLAY LIVE®

MC401 BOOST/ LINE DRIVER



92503004776REVE

MC401 BOOST/LINE DRIVER

DESCRIPTION

 Boost function with knob adjustment from 0 to +20dB of clean uncolored boost

True bypass

POWER

The MXR/CAE Boost/Line Driver is powered by one 9 volt battery (remove bottom plate to install), a 9 volt AC Adapter such as the Dunlop ECB003/ECB003EU or a powersupply such as the DC Brick[™].

DIRECTIONS

• Run a cable from your guitar to the Boost/Line Driver's Input jack and run another cable from the Boost/Linedriver's Output jack to your amplifier.


• Start with the Boost knob at 0dB. Rotate the knob clockwise to increase boost level, up to +20dB.

SPECIFICATIO	ONS
--------------	-----

Input Impedance	1 MΩ
Output Impedance	150 Ω
Nominal Input	-22 dBV
Output Level	-22 dBV
Boost Gain Range	20 dB
Noise Floor*	>95 dB
Bypass	True Hardwire
Current Draw	1.5 mA
Power Supply	9 volts DC

*A-weighted, V_{ref}=1_{Vrms}

CONTROLS





DUNLOP MANUFACTURING, INC. P.O. BOX 846 BENICIA, CA 94510 U.S.A. TEL: 1-707-745-2722 FAX: 1-707-745-2658